

## CLAIMS

I/We claim:

[c1]

1. A memory device comprising:

a memory; and

a plurality of ports for accessing the memory of the memory device, each port having a serial communications link for receiving from and transmitting to an accessing device, each port using plesiosynchronous technique to receive symbols and using in-band symbols to transmit data and out-of-band symbols to transmit control information.

[c2]

2. The memory device of claim 1 wherein each serial communications link is connected to an accessing device via a point-to-point connection.

[c3]

3. The memory device of claim 1 wherein the plesiosynchronous technique oversamples data received via the serial communications link.

[c4]

4. The memory device of claim 1 wherein each port includes a line driver with a fixed driver portion and a variable driver portion for DC-balancing.

[c5]

5. The memory device of claim 1 wherein the memory includes multiple banks and wherein multiple banks can be simultaneously accessed by different ports.

[c6]

6. The memory device of claim 5 wherein each bank includes multiple sections and wherein the multiple sections can be simultaneously accessed by different ports.

- [c7] 7. The memory device of claim 1 wherein the memory includes a bank with multiple sections and wherein the multiple sections can be simultaneously accessed by different ports.
- [c8] 8. The memory device of claim 7 wherein the multiple sections of the bank are configurable on a port-by-port basis.
- [c9] 9. The memory device of claim 8 wherein the configuration information indicates to enable certain sections of the bank.
- [c10] 10. The memory device of 1 wherein the ports are connected to the memory using time-division multiplexing.
- [c11] 11. The memory device of claim 1 wherein the ports are connected to the memory using a crossbar switch.
- [c12] 12. The memory device of claim 1 wherein control information is transmitted as a primitive.
- [c13] 13. The memory device of claim 12 wherein a primitive includes two out-of-band symbols.
- [c14] 14. The memory device of claim 12 wherein control information includes a synchronization symbol.
- [c15] 15. The memory device of claim 1 wherein the plesiosynchronous technique includes inserting or removing symbols to compensate for variations between clock frequencies of the accessing device and the memory device.

[c16] 16. The memory device of claim 1 wherein the ports share a single multiphase clock generator.

[c17] 17. The memory device of claim 16 wherein the multiphase clock generator is a phase lock loop.

[c18] 18. The memory device of claim 1 wherein an out-of-band symbol is a synchronization symbol that encodes a memory command.

[c19] 19. A memory device comprising:  
a memory that reads and writes data;  
a multiphase clock generator that provides a multiphase clock signal; and  
a plurality of ports, each port for connecting to a serial communications link and for receiving data and control information via the serial communications link using a plesiosynchronous technique, wherein each port uses the generated multiphase clock signal generated by the multiphase clock generator.

[c20] 20. The memory device of claim 19 wherein data is sent using in-band symbols and control information is sent via out-of-band symbols.

[c21] 21. The memory device of claim 19 wherein each serial communications link is connected to an accessing device via a point-to-point connection.

[c22] 22. The memory device of claim 19 wherein the plesiosynchronous technique oversamples data received via the serial communications link.

[c23] 23. The memory device of claim 19 wherein each port includes a line driver with a fixed driver portion and a variable driver portion for DC-balancing.

- [c24] 24. The memory device of claim 19 wherein the memory includes multiple banks and wherein multiple banks can be simultaneously accessed by different ports.
- [c25] 25. The memory device of claim 24 wherein each bank includes multiple sections and wherein multiple sections can be simultaneously accessed by different ports.
- [c26] 26. The memory device of claim 19 including multiple sections and wherein multiple sections can be simultaneously accessed by different ports.
- [c27] 27. The memory device of claim 26 wherein the multiple sections are configurable on a port-by-port basis.
- [c28] 28. The memory device of claim 27 including the configuration information storage.
- [c29] 29. The memory device of 19 wherein the ports are connected to the memory using time-division multiplexing.
- [c30] 30. The memory device of claim 19 wherein the ports are connected to the memory using a crossbar switch.
- [c31] 31. The memory device of claim 19 wherein control information is transmitted as a primitive.
- [c32] 32. The memory device of claim 31 wherein a primitive includes two out-of-band symbols.

[c33] 33. The memory device of claim 31 wherein control information includes a synchronization symbol.

[c34] 34. The memory device of claim 19 wherein the plesiosynchronous technique includes inserting or removing symbols to compensate for variations between clock frequencies of the accessing device and the memory device.

[c35] 35. The memory device of claim 19 wherein the multiphase clock generator is a phase lock loop.

[c36] 36. The memory device of claim 19 wherein a synchronization symbol encodes a memory command.

11/01/01 10:00:00 AM